

DGTX10

SAT Dishes



Aluminium offset white dish with 68 cm equivalent diameter. 10 pcs multiple packaging.

Technical Chars

- Steel disc holder with Aluminium/Zinc treatment.
- Aluminium reflectors are best suited for installation in harsh climatic environments.
- Double-focus mount available on all models.
- Single pack models all have a mounting kit ZNCDGT included, for multi pack models the bracket must be ordered separately (ZNCDGTX10 cod. 211110).
- Highest reception quality for all high definition programmes.
- High efficiency and excellent isolation from cross polarisation.
- Available in aluminium or steel in white, grey and brick red colours.
- Fracarro patent.

Data sheet



DGTX10

DGTX10		
Frequency range	MHz	10700-12750
Dimensions	cm	62.4 x 62.4
Offset angle	o	22.3
Efficiency	%	≥ 70
Gain 10.95GHz	dB	36.5
Cross polarization	dB	[°] 37
Side beam	dB	^{<} -32
Noise temperature	°К	40
Fornt back ratio	dB	0.7
Beam width (3dB)	o	3
LNB Clamp	mm	23-28; 40; 60
Elevation angle	o	≤ 60
Mast clamp	mm	35-80
Bracket material		Steel - aluminium/zinc treated
Diameter	cm	68
Material		Aluminium
Colour		White
Dual feed		DFPDIGIT code 211003
Mounting kit		ZNCDGTX10 code 211110
Dimensions and packaging		
Pieces		10
EAN code		8016978007202
Multiple EAN		8016978007219
Packaging dimensions	mm	205 x 690 x 705
Packaging weight	Kg	18.6