

DGTX10-A

SAT Dishes



Steel offset white dish with 68 cm equivalent diameter. 10 pcs multiple packaging.

Technical Chars

- **Disk support made of steel** with Aluminum/Zinc treatment.
- Double fire support available on all models.
- Single-pack models all have ZNCDGT mounting KIT included, for multi-pack the bracket must be ordered separately (ZNCDGTX10 code 211110).
- **Highest reception quality** for all high-definition programs.
- High performance and excellent isolation from cross-polarisation.
- Available in aluminum or steel in white, gray and brick red.
- **Fracarro patent.**

DGTX10-A		
Frequency range	MHz	10700-12750
Dimensions	cm	62.4 x 62.4
Offset angle	°	22.3
Efficiency	%	≥ 70
Gain 10.95GHz	dB	36.5
Cross polarisation	dB	~37
Side beam	dB	~-32
Noise temperature	°K	40
Front back ratio	dB	0.7
Beam width (3dB)	°	3
LNB Clamp	mm	23-28; 40; 60
Elevation angle	°	≤ 60
Mast clamp	mm	35-80
Bracket material	Steel - aluminium/zinc treated	
Diameter	cm	68
Material	Steel	
Colour	White	
Dual feed	DFPDIGIT code 211003	
Mounting kit	ZNCDGTX10 code 211110	
Dimensions and packaging		
Pieces	10	
EAN code	8016978007226	
Multiple EAN	8016978007233	
Packaging dimensions	mm	205 x 690 x 705
Packaging weight	Kg	30