


BLU10HD 5G

UHF Aerials



10 elements UHF band biconical aerial complete with F connector and grid reflectors.

Technical Chars

- Pre-assembled, quick-connect directors, radiator and reflectors on a slide already present on the cradle; **assembly** is completed **without** the use of any **tools**.
- Special care was taken in the choice of materials to achieve higher robustness.
- High gain, excellent impedance matching and excellent directivity.
- Innovative pole mount with zenith adjustment as standard and a knurled surface for optimum strength and hold to the pole, and a **butterfly nut** for **tightening without the need for any tools**.
- An LTE filter has been inserted into the radiator dipole to guarantee the quality of the distributed signal and to obtain excellent filtering of **5G and 4G interfering** signals in the LTE band (694-860 MHz) reserved for mobile telephony.
- White colour aerial.

BLU10HD 5G		
Code		217915
Elements		10
Band		UHF
Channel		E21-E48
Bandwidth	MHz	470-694
Gain	dBi	15.5
Front/Back ratio	dB	30
Return loss	dB	-16
Beam width (3dB)	۰	±24
Wind load 120Km/h 729N/m²	Kg (N)	7.2 (70.6)
Connector		F
Impedence	Ohm	75
Max mast diameter	mm	60
Dimensions	cm	119 x 50
Accessories		
Horizontal polarization		Included



Vertical polarization		Included	
Vertical polarization tilt adjustment		Included	
Auxiliary boom		-	
Dimensions and packaging			
Packing		Single in tray	
Pieces		10	
EAN code		8016978105304	
Multiple EAN		8016978105366	
Packaging dimensions	mm	1250 x 385 x 606	
Packaging weight	Kg	26.75	
Unit weight	Kg	2.22	
Total weight	Kg	24.6	

Gain (x: MHz frequency, y: ISO dBi gain) and Polar diagram (@600MHz)

