

PDM05

Modular walloutlet TV-SAT



Pass through outlet with **5dB** attenuation; **2 demixed outputs** with IEC Male connector for TV band (**47-862MHz**) and F Female connector for Satellite band (**950-2400MHz**).

Technical Chars

- Allows for separation of combined SAT+TV signal input to **2 separate output connectors**.
- Provision is made for **current** flow between the F (SAT) connector and the input/output terminal.
- Equipped with an innovative **flap** for attaching coaxial cables between 4 and 7 mm in diameter.
- Fully shielded(**class A**).
- Plastic **adaptors** available for all popular civil series on the market.
- Complies with EN50083-4.

PDM05		
Code		220002
Type		Passthorough
Insertion loss		
RC 5-40MHz	dB	-
TV 47-862MHz	dB	6
SAT 950-1750MHz	dB	6
SAT 1750-2150MHz	dB	6
SAT 2150-2400MHz	dB	6
Tap loss		
RC 5-40MHz	dB	-
TV 47-862MHz	dB	6
SAT 950-1750MHz	dB	6
SAT 1750-2150MHz	dB	6
SAT 2150-2400MHz	dB	6
Type		Passthorough
Connector		IEC Male, F Female

Dimensions and packaging		
Pieces		10
EAN code		8016978068548
Multiple EAN		8016978068906
Packaging dimensions	mm	114 x 80 x 41
Packaging weight	Kg	0.48