


## PDM14

### Modular walloutlet TV-SAT



**Pass through** outlet with **14dB** attenuation; **2 demixed outputs** with IEC Male connector for TV band (**47-862MHz**) and F Female connector for Satellite band (**950-2400MHz**).

### Technical Chars

- Allows for separation of combined SAT+TV signal input to **2** separate output **connectors**.
- Provision is made for **current** flow between the F (SAT) connector and the input/output terminal.
- Equipped with an innovative **flap** for attaching coaxial cables between 4 and 7 mm in diameter.
- Fully shielded(**class A**).
- Plastic **adaptors** available for all popular civil series on the market.
- Complies with EN50083-4.

PDM14		
Code		220004
Type	Pass through	
Insertion loss		
RC 5-40MHz	dB	-
TV 47-862MHz	dB	3
SAT 950-1750MHz	dB	3.5
SAT 1750-2150MHz	dB	3.5
SAT 2150-2400MHz	dB	3.5
Tap loss		
RC 5-40MHz	dB	-
TV 47-862MHz	dB	14
SAT 950-1750MHz	dB	15
SAT 1750-2150MHz	dB	15
SAT 2150-2400MHz	dB	15
Type	Pass through	
Connector		IEC Male, F Female

Dimensions and packaging		
Pieces		10
EAN code		8016978068562
Multiple EAN		8016978068920
Packaging dimensions	mm	114 x 80 x 41
Packaging weight	Kg	0.48