

SPI14

Modular walloutlet TV-SAT



Pass through outlet with 14dB attenuation; **1 output** with IEC Male connector for TV and Satellite band (**5-2400MHz**).

Technical Chars

- The outlet is designed with an **innovative system to connect to coaxial cable**; it enables the user to connect to a cable with a diameter between 5 and 7mm.
- Fully shielded (**class A**).
- **Plastic adaptors** for all the brands available on the market.
- Complies with EN50083-4.

SPI14		
Code		220714
Type	Passthorough	
Insertion loss		
RC 5-40MHz	dB	1.5
TV 47-862MHz	dB	1.2
SAT 950-1750MHz	dB	2.2
SAT 1750-2150MHz	dB	2.2
SAT 2150-2400MHz	dB	2.5
Tap loss		
RC 5-40MHz	dB	15
TV 47-862MHz	dB	14.5
SAT 950-1750MHz	dB	14.5
SAT 1750-2150MHz	dB	14.5
SAT 2150-2400MHz	dB	15
Type	Passthorough	
Connector	IEC Male	

Dimensions and packaging		
Pieces		4
EAN code		8016978067992
Multiple EAN		8016978068425
Packaging dimensions	mm	75 x 24 x 93
Packaging weight	Kg	0.232