


## MBJ3r3UU T2

### Multiband amplifier



3-input (III+DAB, UHF, UHF) multiband TV indoor amplifier with 32dB gain and up to 120dB $\mu$ V output level on UHF band, separate amplification with independent level adjustment (20dB) for each input and low noise figure. T2 technology with UHF cut band for LTE 4G @790MHz and 5G @694MHz.

### Technical Chars

- **Built-in 5G filter at 694MHz to minimise clutter** in junction boxes compared to the use of an external filter.
- **A.B.L.A. functionality.** FRACARRO's exclusive system for maintaining the set output level constant even when the level of each input changes (independent A.B.L.A. circuits) with **output level stabilisation** even for high variations in the input TV signal and **LED operation** of the dedicated A.B.L.A. circuits.
- **High shielding** against LTE interference (LTE Free)
- Protective shell: the new switchboards are equipped with an ABS fireproof and flame retardant (Class V0) enclosure
- Prepared for **mounting on** a standard **DIN rail** with quick release.
- The dimensions of the MBJ EVO T2 have been designed so that they can be easily installed inside wall boxes.
- **Very high efficiency switching power supply** (>80%) and self-resetting **short-circuit protection** circuit.
- Selector for **remote power supply** on each input (100mA total).
- Power supply status LED.
- Faston for connection to TV system earth.

initial_fields		
Code		223616
Input no.		3
Inputs		III+DAB, UHF, UHF
DAB, III Frequency	MHz	174 - 230
Frequency	MHz	470 - 694
Gain	dB	III+DAB: 32; UHF: 32; UHF: 32
Gain adjustment	dB	III+DAB: 20; UHF: 20; UHF: 20
Optical noise figure	dB	III+DAB: 6; UHF: 9
Outputs number		1
Output level	dB $\mu$ V	III+DAB: 110; UHF: 120
Connectors		F female
Filter		5G

Features		
Power supply voltage	Vac/Hz	220-230 / 50-60
Current consumption	W	6
Isolation class		II
Remote feeding		100mA@12V total
Working temperature	°C	From -10 to +55
Protection		IP20
Dimensions and packaging		
Pcs		1
EAN code		8016978104260
Packaging dimensions	mm	152x105x47
Product dimensions	mm	135x82x39
Packaging weight	Kg	0.345
Weight	Kg	0.34