

MBJ3r3UT2

Multiband amplifier



2-input (III+DAB, UHF) multiband TV indoor amplifier with 35dB gain and up to $120dB\mu V$ output level on UHF band, separate amplification with independent level adjustment (20dB) for each input and low noise figure. T2 technology with UHF cut band for LTE 4G @790MHz and 5G @694MHz.

Technical Chars

- Built-in 5G filter at 694MHz to minimise clutter in junction boxes compared to the use of an external filter.
- A.B.L.A. functionality. fRACARRO's exclusive system for maintaining the set output level constant even when the level of each input changes (independent A.B.L.A. circuits) with **output level stabilisation** even for high variations in the input TV signal and **LED operation of** the dedicated A.B.L.A. circuits.
- High shielding against LTE interference (LTE Free)
- Protective shell: the new switchboards are equipped with an ABS fireproof and flame retardant (Class V0) enclosure
- Prepared for mounting on a standard DIN rail with quick release.
- The dimensions of the MBJ EVO T2 have been designed so that they can be easily installed inside wall boxes.
- Very high efficiency switching power supply (>80%) and self-resetting short-circuit protection circuit.
- Selector for remote power supply on each input (100mA total).
- Power supply status LED.
- Faston for connection to TV system earth.

| initial_fields | | |
|----------------------|------|------------------------|
| Code | | 223621 |
| Input no. | | 2 |
| Inputs | | III+DAB, UHF |
| DAB, III Frequency | MHz | 174 - 230 |
| Frequency | MHz | 470 - 694 |
| Gain | dB | III+DAB: 35; UHF: 35 |
| Gain adjustment | dB | III+DAB: 20; UHF: 20 |
| Optical noise figure | dB | III+DAB: 6; UHF: 6 |
| Outputs number | | 1 |
| Output level | dΒμV | III+DAB: 110; UHF: 120 |
| Connectors | | F female |
| Filter | | 5G |



| Specifications | | |
|--------------------------|-------|-----------------|
| Power supply voltage | Vdc/A | 220-230 / 50-60 |
| Current consumption | W | 6 |
| Isolation class | | II |
| Remote feeding | | 100mA@12V total |
| Operating temperature | °C | -10 to +55 |
| Protection | | IP20 |
| Dimensions and packaging | | |
| Pieces | | 1 |
| EAN code | | 8016978104345 |
| Packaging dimensions | mm | 152 x 105 x 47 |
| Product dimensions | mm | 135 x 82 x 39 |
| Packaging weight | Kg | 0.345 |
| Weight | Kg | 0.34 |