

MAP4rU LTE700+K

Mast amplifier



1-input (UHF) mast amplifier with 42dB gain and up to $116dB\mu V$ output level on UHF band, gain adjustment 0-15dB and low noise figure. 694MHz 5G and 4G LTE integrated filter. Power supply included in the package.

Technical Chars

- CLIPPER Technology: exclusive system that limits the gain of the UHF band of the device to guarantee the maximum RF output level available and minimise intermodulation; an LED lights up when this control is activated.
- RED Compliant: each model complies with the regulatory requirements regarding Radio Spectrum, Electromagnetic Compatibility and Safety set out in recent European directives.
- ZAMA die-cast frame with metal covers for extremely high interference shielding (LTE Free).
- The **ABS outdoor protective hood** is equipped with a slide opening and tilting system for the amplifier section, making the installer's work easier.
- Selector switch for switching the **remote power supply to the UHF input**, or to the V+U input depending on the model.
- Status LED for correct power supply and fixing clamp suitable for poles up to 60mm diameter.

initial_fields		
Code		223718
Input no.		1
Inputs		UHF
Frequency	MHz	470 - 694
Gain	dB	UHF. 42
Gain adjustment	dB	UHF: 15
Optical noise figure	dB	UHF: 3
Outputs number		1
Output level	dΒμV	UHF: 116
Connectors		F female
Clipper		Sì
Filter		5G



Specifications		
Power supply voltage	V	24
Absorption	mA	100 @24V
Impedence	Ohm	75
Operating temperature	°C	-10 to +55
Protection		IP43
Conformity		EN50083-2: 2006-06
Dimensions and packaging		
Pieces		1
EAN code		8016978101658
Packaging dimensions	mm	128 x 111 x 111
Product dimensions	mm	120 x 50 x 105
Packaging weight	Kg	0.540
Weight	Kg	0.500