

MAP4r3UU T2+ K

Mast amplifier



3-input (III+DAB, UHF, UHF) mast amplifier with 40dB gain and up to 116dBµV output level on UHF band, separate VHF/UHF amplification with independent gain adjustment (0-15dB) for each input and low noise figure. T2 technology with UHF cut band for LTE 4G @790MHz and 5G @694MHz. Power supply included in the package.

Technical Chars

- Internal 5G filter at 694MHz to give connections more protection from interference than an external filter.
- CLIPPER Technology: unique system that limits the UHF band gain of the device to ensure the maximum RF output level available and minimize intermodulation; there is an LED that lights up when this control is activated.
- **RED Compliant**: each model complies with the regulatory requirements regarding Radio Spectrum Electromagnetic Compatibility and Safety set forth in recent European directives.
- ZAMA die-cast frame with metal covers for very high shielding to interference (LTE Free).
- Outdoor protective bell made of ABS is equipped with a slide opening and tilting system of the amplification section to make the installer's work easier.
- Selector switch for inserting tele-power on the UHF input, or on the V+U input depending on the model.
- Status LED for correct power supply and fixing clamp suitable for poles up to 60mm diameter.

initial_fields		
Code		223742
Input no.		3
Inputs		III+DAB, UHF, UHF
DAB, III Frequency	MHz	174 - 240
Frequency	MHz	470 - 694
Gain	dB	III+DAB: 22; UHF 40; UHF 40
Gain adjustment	dB	III+DAB: 15; UHF 15; UHF 15
Optical noise figure	dB	III+DAB: 5; UHF: 7
Outputs number		1
Output level	dΒμV	III+DAB: 112; UHF: 116
Connectors		F female
Clipper		Sì
Filter		5G



Specifications		
Power supply voltage	V	12
Absorption	mA	125 @12V
Impedence	Ohm	75
Operating temperature	°C	-10 to +55
Protection		IP43
Conformity		EN50083-2: 2006-06
Dimensions and packaging		
Pieces		1
EAN code		8016978105090
Packaging dimensions	mm	128 x 111 x 111
Product dimensions	mm	120 x 50 x 105
Packaging weight	Kg	0.545
Weight	Kg	0.520