

## MAP4r3+U T2+ K

Mast amplifier



1-input (III+DAB+UHF) mast amplifier with 42dB gain and up to 116dBµV output level on UHF band, separate VHF/UHF amplification with independent gain adjustment (0-15dB) for each band and low noise figure. T2 technology with UHF cut band for LTE 4G @790MHz and 5G @694MHz. **Power supply included in the package.** 

## **Technical Chars**

- Internal 5G filter at 694MHz to give connections more protection from interference than an external filter.
- **CLIPPER Technology**: unique system that limits the UHF band gain of the device to **ensure the maximum** RF **output level** available and minimize intermodulation; there is an **LED** that lights up when this control is activated.
- **RED Compliant**: each model complies with the regulatory requirements regarding Radio Spectrum Electromagnetic Compatibility and Safety set forth in recent European directives.
- ZAMA die-cast frame with metal covers for very high shielding to interference (LTE Free).
- Outdoor protective bell made of ABS is equipped with a slide opening and tilting system of the amplification section to make the installer's work easier.
- Selector switch for inserting tele-power on the UHF input, or on the V+U input depending on the model.
- Status LED for correct power supply and fixing clamp suitable for poles up to 60mm diameter.

initial_fields		
Code		223743
Input no.		1
Inputs		III+DAB + UHF
DAB, III Frequency	MHz	174 - 240
Frequency	MHz	470 - 694
Gain	dB	III+DAB: 22; UHF: 42
Gain adjustment	dB	III+DAB: 15; UHF: 15
Optical noise figure	dB	III+DAB: 6; UHF: 4
Outputs number		1
Output level	dBµV	III+DAB: 112; UHF: 116
Connectors		F female
Clipper		Sì
Filter		5G

## Data sheet



## Specifications

V	12
mA	125 @12V
Ohm	75
°C	-10 to +55
	IP43
	EN50083-2: 2006-06
	1
	8016978105106
mm	128 x 111 x 111
mm	120 x 50 x 105
Kg	0.545
Kg	0.520
	mA Ohm °C