

## OPT RX 4 MICRO

Home fibre



Optical TV SAT receiver with universal legacy 4SAT+TV+FM outputs, SC/APC optical connector

### Technical Chars

- Low current consumption
- Standard SC/APC optical connector
- Quick and easy installation due to very small dimensions
- Optical budget: up to 21dB
- Optical range extended reception (**from -8dBmo to -14dBmo**)
- Full band: 87-862 for TV / 950-2150 for SAT polarities
- Multi-function LEDs: power status and signalling.

OPT RX 4 MICRO		
Code		270662
Optical input		
Optical input connector		1 SC/APC
Wavelength input	nm	1260-1650
Optical input power	dBm	≤ -8
RF output		
Connectors type		F Female
Return loss	dB	-10
Outputs		4 SAT (VL,HL,VH,HH)+ 1 TV
Output level TV		
8dBmo 8 transponder	dBμV	85
8dBmo 16 transponder	dBμV	82
8dBmo 40 transponder	dBμV	78
14dBmo 8 transponder	dBμV	67
14dBmo 16 transponder	dBμV	64
14dBmo 40 transponder	dBμV	66
Output level SAT		
14dBmo	dBμV	68@TP

Features		
Power supply voltage	V	14/18 from all exits
Current consumption	mA	180@13V
Current consumption	W	2.5
LED		<ul style="list-style-type: none"> <li>• Green LED on: normal operation (properly powered)</li> <li>• LED flashing quickly: hardware anomaly</li> <li>• LED flashing slowly: optical power out of the operating range</li> </ul>
Working temperature	°C	From -5 to +50
Conformity		CEI EN 50083-2 EN60065
Dimensions and packaging		
Pcs		1
EAN code		8016978101344
Packaging dimensions	mm	130x110x37
Product dimensions	mm	120x100x36
Packaging weight	Kg	0.312