

SWA5122

Line amplifiers



Line amplifier with 2 inputs (1 Satellite and 1 TV).

Technical Chars

- High TV amplification.
- **Gain and slope adjustment for TV input.**
- Gain adjustment for return channel.
- High TV output level.
- Remote powered via Satellite line.
- Ideal for medium and large installations or where there are long distances between multiswitches.
- Easy to install due to standard colouring of inputs.

| SWA5122 | | |
|---------------------|------------|-------------|
| Code | | 271035 |
| Inputs | | 1 SAT, 1 TV |
| Outputs | | 1 SAT, 1 TV |
| SAT | | |
| Bandwidth | MHz | 950-2150 |
| Gain | dB | -1 |
| TV | | |
| TV bandwidth | MHz | 5-862 |
| Gain (Active) | dB | 30 |
| Gain adjustment | dB | 15 |
| TV tilt adjustment | dB | 15 |
| Max Output level | dB μ V | 116 |
| Return channel | | |
| Bandwidth | MHz | 5-65 |
| Gain | dB | 15 |
| Gain adjustment | dB | 10 |
| RC max output level | dB μ V | 106 |

| Consumption | | |
|--------------------------|----|---------------------|
| Power supply voltage | V | 14-30 (on SAT line) |
| Absorption | mA | 400 @14V |
| Specifications | | |
| Operating temperature | °C | -10 to +55 |
| Dimensions and packaging | | |
| Pieces | | 1 |
| EAN code | | 8016978065370 |
| Packaging dimensions | mm | 215 x 125 x 35 |
| Product dimensions | mm | 198 x 108 x 30 |
| Packaging weight | Kg | 0.45 |