

SWI8532STPLUS

Cascadable

5-input cascadable multiswitch with **32 output taps**; **active gain** and separate TV and Satellite gain Adjustment (independent for low and high bands). **Coupled chassis**.

Technical Chars

- **TV gain adjustment.**
- **2 settings for Satellite signal gain**, separate high-band and low-band.
- High isolation (> 45dB).
- Low pass loss.
- **Very high output level** to cover long cable distances(**100m** with 6.7mm cable).
- Return channel included.
- Low power consumption.
- Easy to install due to standard input colouring

SWI8532STPLUS		
Code		271058
Inputs		4 SAT, 1 TV
Outputs		4 SAT, 1 TV
Taps		32
SAT		
Bandwidth	MHz	950-2150
Gain	dB	-2/4
Gain adjustment	dB	15
Max Output level	dB μ V	108
Insertion loss	dB	-5
TV		
TV bandwidth	MHz	85-862
Gain (Active)	dB	-10/-4
Gain adjustment	dB	20
Max Output level	dB μ V	102
Insertion loss	dB	-4
Return channel		
Bandwidth	MHz	5-65
Gain	dB	-6
RC max output level	dB μ V	100
Insertion loss	dB	-2
Consumption		
Absorption	mA	440@14V; 340@18V

Specifications		
Operating temperature	°C	-10 to +55
SAT-SAT Isolation	dB	>45
Dimensions and packaging		
Pieces		1
EAN code		8016978084708
Packaging dimensions	mm	590 x 175 x 75
Product dimensions	mm	440 x 120 x 60
Packaging weight	Kg	2.3