

## SWI4406-00

Cascadable



4-input cascadable multiswitch with 6 output taps and 0dB attenuation.

### Technical Chars

- The series consists of 3 different attenuation levels (-17dB, -8dB, 0dB) to equalise the signal distribution between planes and facilitate the construction of a complex distribution network.
- Low pass loss.
- **High output level** to cover long cable distances(70m with 6.7mm cable).
- **The multiswitch is fully powered by the decoder.**
- **The LNB can be powered by the decoder even when only one user is connected or along its passing lines.**
- Plastic bracket for quick and easy installation.
- Easy to install thanks to the standard colouring of the inputs.

SWI4406-00		
Code		271084
Inputs		4 SAT
Outputs		4 SAT
Taps		6 SAT
SAT		
Bandwidth	MHz	950-2150
Gain	dB	0
Max Output level	dB $\mu$ V	105
Insertion loss	dB	-2
Consumption		
Tap	mA	35
Specifications		
Operating temperature	$^{\circ}$ C	-10 to +55
SAT-SAT Isolation	dB	>28

Dimensions and packaging		
Pieces		1
EAN code		8016978068319
Packaging dimensions	mm	145 x 90 x 35
Product dimensions	mm	119 x 70 x 20
Packaging weight	Kg	0.23