


SWP516QD

Compact



5-input compact multiswitch with 16 output taps; active gain on TV and Satellite bands and compatibility with QUAD and QUATTRO LNBs.

Technical Chars

- **TV (+5dB) and Satellite (+5dB) gains active**, ensuring the same signal received at the output as at the input.
- Satellite bandwidth up to 2300MHz.
- **Compatibility with QUAD (UX-QD L TE) and QUATTRO (UX-QT LTE)LNB types.**
- **High output level** to cover long cable distances(**70m** with 6.7mm cable).
- Low power consumption thanks to automatic detection circuit for the necessary power supply on Satellite and TV lines.
- **External power supply with jack connector included in the PSU1220JA package;** to optimise installation space and reduce maintenance time.
- Small size due to matrix switching system, with connectors on both sides.
- Easy to install thanks to standard input colouring.

SWP516QD		
Code		271166
Inputs		4 SAT, 1 TV
Taps		16
SAT		
Bandwidth	MHz	950-2400
Gain	dB	5
Max Output level	dBμV	102
TV		
TV bandwidth	MHz	85-790
Gain (Active)	dB	0
Max Output level	dBμV	95

Consumption		
Tap	mA	35
Power supply voltage	Vdc/A	220-240 / 50-60
Current consumption without LNB	mA	300 @12V
Current consumption with LNB	mA	1000 @12V
Max current consumption LNB	mA	300
Maximum power supply current TV	mA	170
Specifications		
Dimensions power supply	mm	78x48x35
Operating temperature	°C	-10 to +55
SAT-SAT Isolation	dB	>25
TV-SAT Isolation	dB	>25
Dimensions and packaging		
Pieces		1
EAN code		8016978099313
Packaging dimensions	mm	428 x 175 x 75
Product dimensions	mm	260 x 120 x 25
Packaging weight	kg	0.981