

DE1-14

Taps and splitters



Vertical 1-way shunt with 14dB attenuation and F connector in TV and Satellite band(5-2400MHz).

Technical Chars

- The elegant and compact design allows installation in any junction box.
- **Die-cast and nickel-plated**, it ensures high performance, with very low insertion loss, high return loss and insulation.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the feed-through output and the input.**

DE1-14		
Code		280711
Taps		1
Insertion loss		
RC 5-40MHz	dB	1
TV 47-862MHz	dB	0.8
SAT 950-1750MHz	dB	1.2
SAT 1750-2150MHz	dB	1.3
SAT 2150-2400MHz	dB	1.5
Tap loss		
RC 5-40MHz	dB	14
TV 47-862MHz	dB	14
SAT 950-1750MHz	dB	14
SAT 1750-2150MHz	dB	14
SAT 2150-2400MHz	dB	14
Outputs Isolation		
RC 5-40MHz	dB	32
TV 47-862MHz	dB	29
SAT 950-1750MHz	dB	28
SAT 1750-2150MHz	dB	30
SAT 2150-2400MHz	dB	25

Specifications		
Tap loss	dB	14
Dimensions and packaging		
Pieces		10
EAN code		8016978007547
Multiple EAN		8016978007554
Packaging dimensions	mm	150 x 110 x 50
Packaging weight	Kg	0.56