

DE1-22

Taps and splitters



1-way vertical shunt with 22dB attenuation and F connector in TV and Satellite band(5-2400MHz).

Technical Chars

- The elegant and compact design allows installation in any junction box.
- **Die-cast and nickel-plated**, it ensures high performance, with very low insertion loss, high return loss and insulation.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the feed-through output and the input.**

DE1-22		
Code		280713
Taps		1
Insertion loss		
RC 5-40MHz	dB	0.6
TV 47-862MHz	dB	0.5
SAT 950-1750MHz	dB	0.8
SAT 1750-2150MHz	dB	1
SAT 2150-2400MHz	dB	1.7
Tap loss		
RC 5-40MHz	dB	22
TV 47-862MHz	dB	22
SAT 950-1750MHz	dB	22
SAT 1750-2150MHz	dB	22
SAT 2150-2400MHz	dB	22
Outputs Isolation		
RC 5-40MHz	dB	50
TV 47-862MHz	dB	36
SAT 950-1750MHz	dB	33
SAT 1750-2150MHz	dB	31
SAT 2150-2400MHz	dB	27

Specifications		
Tap loss	dB	22
Dimensions and packaging		
Pieces		10
EAN code		8016978007585
Multiple EAN		8016978007592
Packaging dimensions	mm	150 x 110 x 50
Packaging weight	Kg	0.56