

## DE2-10

### Taps and splitters



Vertical 2-way shunt with 10dB attenuation and F connector in TV and Satellite band(5-2400MHz).

### Technical Chars

- The elegant and compact design allows installation in any junction box.
- **Die-cast and nickel-plated**, it ensures high performance, with very low insertion loss, high return loss and insulation.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the feed-through output and the input.**

DE2-10		
Code		280714
Taps		2
Insertion loss		
RC 5-40MHz	dB	2.5
TV 47-862MHz	dB	2.5
SAT 950-1750MHz	dB	2.5
SAT 1750-2150MHz	dB	2.8
SAT 2150-2400MHz	dB	3.5
Tap loss		
RC 5-40MHz	dB	10
TV 47-862MHz	dB	10
SAT 950-1750MHz	dB	10
SAT 1750-2150MHz	dB	10
SAT 2150-2400MHz	dB	10
Outputs Isolation		
RC 5-40MHz	dB	25
TV 47-862MHz	dB	28
SAT 950-1750MHz	dB	25
SAT 1750-2150MHz	dB	25
SAT 2150-2400MHz	dB	23

Specifications		
Tap loss	dB	10
Dimensions and packaging		
Pieces		10
EAN code		8016978007608
Multiple EAN		8016978007615
Packaging dimensions	mm	150 x 110 x 50
Packaging weight	Kg	0.56