

DE2-18

Taps and splitters



2-way vertical shunt with 18dB attenuation and F connector in TV and Satellite band(5-2400MHz).

Technical Chars

- The elegant and compact design allows installation in any junction box.
- **Die-cast and nickel-plated**, it ensures high performance, with very low insertion loss, high return loss and insulation.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the feed-through output and the input.**

| DE2-18 | | |
|-------------------|----|--------|
| Code | | 280716 |
| Taps | | 2 |
| Insertion loss | | |
| RC 5-40MHz | dB | 1.2 |
| TV 47-862MHz | dB | 1.2 |
| SAT 950-1750MHz | dB | 1.5 |
| SAT 1750-2150MHz | dB | 1.8 |
| SAT 2150-2400MHz | dB | 2 |
| Tap loss | | |
| RC 5-40MHz | dB | 18 |
| TV 47-862MHz | dB | 18 |
| SAT 950-1750MHz | dB | 18 |
| SAT 1750-2150MHz | dB | 18 |
| SAT 2150-2400MHz | dB | 19 |
| Outputs Isolation | | |
| RC 5-40MHz | dB | 45 |
| TV 47-862MHz | dB | 33 |
| SAT 950-1750MHz | dB | 27 |
| SAT 1750-2150MHz | dB | 27 |
| SAT 2150-2400MHz | dB | 25 |

| Specifications | | |
|--------------------------|----|----------------|
| Tap loss | dB | 18 |
| Dimensions and packaging | | |
| Pieces | | 10 |
| EAN code | | 8016978007646 |
| Multiple EAN | | 8016978007653 |
| Packaging dimensions | mm | 150 x 110 x 50 |
| Packaging weight | Kg | 0.56 |