DE2-18

Taps and splitters

2-way vertical shunt with **18dB** attenuation and F connector in TV and Satellite band**(5-2400MHz)**.

Technical Chars

- The elegant and compact design allows installation in any junction box.
- **Die-cast and nickel-plated**, it ensures high performance, with very low insertion loss, high return loss and insulation.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the feed-through output and the input.**

DE2-18		
Code		280716
Taps		2
Insertion loss		
RC 5-40MHz	dB	1.2
TV 47-862MHz	dB	1.2
SAT 950-1750MHz	dB	1.5
SAT 1750-2150MHz	dB	1.8
SAT 2150-2400MHz	dB	2
Tap loss		
RC 5-40MHz	dB	18
TV 47-862MHz	dB	18
SAT 950-1750MHz	dB	18
SAT 1750-2150MHz	dB	18
SAT 2150-2400MHz	dB	19
Outputs Isolation		
RC 5-40MHz	dB	45
TV 47-862MHz	dB	33
SAT 950-1750MHz	dB	27
SAT 1750-2150MHz	dB	27
SAT 2150-2400MHz	dB	25

Specifications		
Tap loss	dB	18
Dimensions and packaging		
Pieces		10
EAN code		8016978007646
Multiple EAN		8016978007653
Packaging dimensions	mm	150 x 110 x 50
Product dimensions	mm	41 x 35 x 25
Packaging weight	Kg	0.56