

DE2-22

Taps and splitters



Vertical 2-way shunt with 22dB attenuation and F connector in TV and Satellite band(5-2400MHz).

Technical Chars

- The elegant and compact design allows installation in any junction box.
- **Die-cast and nickel-plated**, it ensures high performance, with very low insertion loss, high return loss and insulation.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the feed-through output and the input.**

DE2-22		
Code		280717
Taps		2
Insertion loss		
RC 5-40MHz	dB	1.2
TV 47-862MHz	dB	1.1
SAT 950-1750MHz	dB	1.5
SAT 1750-2150MHz	dB	1.8
SAT 2150-2400MHz	dB	2.2
Tap loss		
RC 5-40MHz	dB	22
TV 47-862MHz	dB	22
SAT 950-1750MHz	dB	22
SAT 1750-2150MHz	dB	22
SAT 2150-2400MHz	dB	22
Outputs Isolation		
RC 5-40MHz	dB	45
TV 47-862MHz	dB	38
SAT 950-1750MHz	dB	31
SAT 1750-2150MHz	dB	27
SAT 2150-2400MHz	dB	27

Specifications		
Tap loss	dB	22
Dimensions and packaging		
Pieces		10
EAN code		8016978007660
Multiple EAN		8016978007677
Packaging dimensions	mm	150 x 110 x 50
Packaging weight	Kg	0.56