

## DE4-12

### Taps and splitters



**4-way vertical shunt** with 12dB attenuation and F connector in TV and Satellite band(5-2400MHz).

### Technical Chars

- The elegant and compact design allows installation in any junction box.
- **Die-cast and nickel-plated**, it ensures high performance, with very low insertion loss, high return loss and insulation.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the feed-through output and the input.**

DE4-12		
Code		280718
Taps		4
Insertion loss		
RC 5-40MHz	dB	3.5
TV 47-862MHz	dB	3.9
SAT 950-1750MHz	dB	5.1
SAT 1750-2150MHz	dB	5.2
SAT 2150-2400MHz	dB	5.4
Tap loss		
RC 5-40MHz	dB	11.5
TV 47-862MHz	dB	11.5
SAT 950-1750MHz	dB	13
SAT 1750-2150MHz	dB	14
SAT 2150-2400MHz	dB	15.5
Outputs Isolation		
RC 5-40MHz	dB	35
TV 47-862MHz	dB	33
SAT 950-1750MHz	dB	28
SAT 1750-2150MHz	dB	28
SAT 2150-2400MHz	dB	28

Specifications		
Tap loss	dB	12
Dimensions and packaging		
Pieces		10
EAN code		8016978007684
Multiple EAN		8016978007691
Packaging dimensions	mm	150 x 110 x 50
Packaging weight	Kg	0.56