

DE4-14

Taps and splitters



4-way vertical shunt with 14dB attenuation and F connector in TV and Satellite band(5-2400MHz).

Technical Chars

- The elegant and compact design allows installation in any junction box.
- **Die-cast and nickel-plated**, it ensures high performance, with very low insertion loss, high return loss and insulation.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the feed-through output and the input.**

DE4-14		
Code		280719
Taps		4
Insertion loss		
RC 5-40MHz	dB	2.5
TV 47-862MHz	dB	2.4
SAT 950-1750MHz	dB	3
SAT 1750-2150MHz	dB	3.5
SAT 2150-2400MHz	dB	4
Tap loss		
RC 5-40MHz	dB	14.5
TV 47-862MHz	dB	13.8
SAT 950-1750MHz	dB	14
SAT 1750-2150MHz	dB	14.5
SAT 2150-2400MHz	dB	15
Outputs Isolation		
RC 5-40MHz	dB	32
TV 47-862MHz	dB	34
SAT 950-1750MHz	dB	30
SAT 1750-2150MHz	dB	27
SAT 2150-2400MHz	dB	30

Specifications		
Tap loss	dB	14
Dimensions and packaging		
Pieces		10
EAN code		8016978007707
Multiple EAN		8016978007714
Packaging dimensions	mm	150 x 105 x 65
Packaging weight	Kg	0.84