

DE4-22

Taps and splitters



4-output vertical tap with 22dB attenuation and F connector for TV and Satellite band (**5-2400MHz**).

Technical Chars

- The elegant and compact design allows installation in any junction box.
- **Die-cast and nickel-plated**, it ensures high performance, with very low insertion loss, high return loss and insulation.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the feed-through output and the input.**

DE4-22		
Code		280721
Taps		4
Insertion loss		
RC 5-40MHz	dB	1
TV 47-862MHz	dB	1
SAT 950-1750MHz	dB	1.2
SAT 1750-2150MHz	dB	1.5
SAT 2150-2400MHz	dB	1.5
Tap loss		
RC 5-40MHz	dB	21.5
TV 47-862MHz	dB	21.8
SAT 950-1750MHz	dB	22.5
SAT 1750-2150MHz	dB	23
SAT 2150-2400MHz	dB	24
Outputs Isolation		
RC 5-40MHz	dB	38
TV 47-862MHz	dB	35
SAT 950-1750MHz	dB	31
SAT 1750-2150MHz	dB	27
SAT 2150-2400MHz	dB	26

Specifications		
Tap loss	dB	22
Dimensions and packaging		
Pieces		10
EAN code		8016978007745
Multiple EAN		8016978007752
Packaging dimensions	mm	150 x 110 x 60
Packaging weight	Kg	0.82