


DE8-16

Taps and splitters



8-output vertical tap with 16dB attenuation and F connector for TV and Satellite band (**5-2400MHz**).

Technical Chars

- The elegant and compact design allows installation in any junction box.
- **Die-cast and nickel-plated**, it ensures high performance, with very low insertion loss, high return loss and insulation.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the feed-through output and the input.**

DE8-16		
Code		280725
Taps		8
Insertion loss		
RC 5-40MHz	dB	4.5
TV 47-862MHz	dB	5
SAT 950-1750MHz	dB	5.5
SAT 1750-2150MHz	dB	5.5
SAT 2150-2400MHz	dB	5.5
Tap loss		
RC 5-40MHz	dB	14
TV 47-862MHz	dB	15
SAT 950-1750MHz	dB	16.5
SAT 1750-2150MHz	dB	18
SAT 2150-2400MHz	dB	19.5
Outputs Isolation		
RC 5-40MHz	dB	30
TV 47-862MHz	dB	25
SAT 950-1750MHz	dB	25
SAT 1750-2150MHz	dB	25
SAT 2150-2400MHz	dB	25

Specifications		
Tap loss	dB	16
Dimensions and packaging		
Pieces		10
EAN code		8016978034871
Multiple EAN		8016978035076
Packaging dimensions	mm	310 x 125 x 50
Packaging weight	Kg	1.4