


DE8-20

Taps and splitters



8-output vertical tap with 20dB attenuation and F connector for TV and Satellite band (**5-2400MHz**).

Technical Chars

- The elegant and compact design allows installation in any junction box.
- **Die-cast and nickel-plated**, it ensures high performance, with very low insertion loss, high return loss and insulation.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the feed-through output and the input.**

| DE8-20 | | |
|-------------------|----|--------|
| Code | | 280726 |
| Taps | | 8 |
| Insertion loss | | |
| RC 5-40MHz | dB | 2.5 |
| TV 47-862MHz | dB | 3 |
| SAT 950-1750MHz | dB | 4.5 |
| SAT 1750-2150MHz | dB | 5 |
| SAT 2150-2400MHz | dB | 5.5 |
| Tap loss | | |
| RC 5-40MHz | dB | 19 |
| TV 47-862MHz | dB | 19 |
| SAT 950-1750MHz | dB | 19 |
| SAT 1750-2150MHz | dB | 19 |
| SAT 2150-2400MHz | dB | 20 |
| Outputs Isolation | | |
| RC 5-40MHz | dB | 30 |
| TV 47-862MHz | dB | 23 |
| SAT 950-1750MHz | dB | 20 |
| SAT 1750-2150MHz | dB | 20 |
| SAT 2150-2400MHz | dB | 20 |

| Specifications | | |
|--------------------------|----|----------------|
| Tap loss | dB | 20 |
| Dimensions and packaging | | |
| Pieces | | 10 |
| EAN code | | 8016978034888 |
| Multiple EAN | | 8016978035083 |
| Packaging dimensions | mm | 310 x 125 x 50 |
| Product dimensions | mm | 101 x 51 x 25 |
| Packaging weight | Kg | 1.4 |