

3DG-4S2-BP

Modular



3DGFLEX series, transmodulation from DVB-S2/T2/C to DVB-T, modular

Technical Chars

initial_fields		
Code		283163
Input		
Input no.		4
Input level	dB μ V	50-80
Demodulators		DVB-S2 (8-PSK, QPSK), DVB-S (QPSK)
Input band		950-2150
Input AFC	MHz	\pm 5
Symbol rate	Mbps	2-45
FEC		1/2, 2/3, 3/4, 5/6, 7/8, AUTO
Remote feeding	mA	4x125 max (14/18V)
LNB controls		DiSEqC 1.0
IP output		
Connectors		4
Back panel		
Output type TS		Serial
TS outputs		48 pins on Back Panel
TS max bitrate	Mbps	1000 bidirectional

Features		
Connectors		SW update and video playback (type A, FAT32 filesystem, .TS file playback)
Programming mode		Web interface, keyboard and front display
Current consumption	W	7 (senza CAM), 12 (con CAM)
Common interface		2 x PCMCIA (Standard EN50221, TS10169) Flex CAM or Standard Mode
Working temperature	°C	From -10 to 50; from -10 to 45 (with CAM)
Conformity		EN50083-2, EN60065
Dimensions and packaging		
Pcs		1
EAN code		8016978099337
Packaging dimensions	mm	305x220x82
Product dimensions	mm	245x208x54
Packaging weight	Kg	1.14