

3DG-4T2-BP

Modular



3DGFLEX series, transmodulation from DVB-S2/T2/C to DVB-T, modular

Technical Chars

initial_fields		
Code		283166
Input		
Input no.		4
Input level	dB μ V	40-85
Demodulators		DVB-T2, DVB-T o DVB-C (selectable)
Input band		174-862
Channel		E5-E69
Input AFC	MHz	\pm 400 (DVB-T2/T), \pm 100 (DVB-C)
FEC		1/2, 2/3, 3/4, 5/6, 7/8 Reed Solomon (204, 188)
Remote feeding	mA	2 x 100 max (12V)
IP output		
Connectors		4
Back panel		
Output type TS		Serial
TS outputs		48 pins on Back Panel
TS max bitrate	Mbps	1000 (bidirectional)
Features		
Connectors		SW update and video playback (type A, FAT32 filesystem, .TS file playback)
Programming mode		Web interface, keyboard and front display
Current consumption	W	7 (senza CAM), 12 (con CAM)
Common interface		2 x PCMCIA (Standard EN50221, TS10169) Flex CAM or Standard Mode
Working temperature	$^{\circ}$ C	From -10 to 50; from -10 to 45 (with CAM)
Conformity		EN50083-2, EN60065

Dimensions and packaging		
Pcs		1
EAN code		8016978100088
Packaging dimensions	mm	305x220x85
Product dimensions	mm	245x208x54
Packaging weight	Kg	1.126