3DG-4T2-BP

Modular

3DGFLEX series, transmodulation from DVB-S2/T2/C to DVB-T, modular

initial_fields		
Code		283166
Input		
Input no.		4
Input level	dBµV	40-85
Demodulators		DVB-T2, DVB-T o DVB-C (selectable)
Input band		174-862
Channel		E5-E69
Input AFC	MHz	±400 (DVB-T2/T), ±100 (DVB-C)
FEC		1/2, 2/3, 3/4, 5/6, 7/8 Reed Solomon (204, 188)
Remote feeding	mA	2 x 100 max (12V)
IP output		
Connectors		4
Back panel		
Output type TS		Serial
TS outputs		48 pins on Back Panel
TS max bitrate	Mbps	1000 (bidirectional)
Specifications		
Connectors		SW update and video playback (type A, FAT32 filesystem, .TS file playback)
Programming mode		Web interface, keyboard and front display
Current consumption	W	7 (without CAM), 12 (with CAM)
Common interface		2 x PCMCIA (Standard EN50221, TS10169) Flex CAM or Standard Mode
Operating temperature	°C	-10 to 50; -10 to 45 (with CAM)
Conformity		EN50083-2, EN60065

Dimensions and packaging		
Pieces		1
EAN code		8016978100088
Packaging dimensions	mm	305 x 220 x 85
Product dimensions	mm	245 x 208 x 54
Packaging weight	Kg	1.126