

TAPS220

Taps and splitters



2-output "top-down" horizontal tap with 20dB attenuation and F connector for TV and Satellite band (5-2400MHz).

Technical Chars

- The elegant and compact design allows installation in any junction box.
- The **die-cast zinc** products in this series ensure high performance, with very low insertion losses even at SAT frequencies and high isolation between outputs.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the through output and input.**

TAPS220		
Code		287315
Taps		2
Insertion loss		
RC 5-40MHz	dB	1.5
TV 47-862MHz	dB	2
SAT 950-1750MHz	dB	3
SAT 1750-2150MHz	dB	3
SAT 2150-2400MHz	dB	4
Tap loss		
RC 5-40MHz	dB	20
TV 47-862MHz	dB	20
SAT 950-1750MHz	dB	20
SAT 1750-2150MHz	dB	20
SAT 2150-2400MHz	dB	20
Outputs Isolation		
RC 5-40MHz	dB	33
TV 47-862MHz	dB	30
SAT 950-1750MHz	dB	28
SAT 1750-2150MHz	dB	28
SAT 2150-2400MHz	dB	25

Specifications

Tap loss	dB	20
----------	----	----

Dimensions and packaging

Pieces		1
EAN code		8016978094974
Packaging dimensions	mm	55 x 64 x 27
Product dimensions	mm	55 x 64 x 27
Packaging weight	Kg	0.085