


TAPS616

Taps and splitters

6-output "top-down" horizontal tap with 16dB attenuation and F connector for TV and Satellite band (5-2400MHz).



Technical Chars

- The elegant and compact design allows installation in any junction box.
- The **die-cast zinc** products in this series ensure high performance, with very low insertion losses even at SAT frequencies and high isolation between outputs.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the through output and input.**

TAPS616		
Code		287319
Taps		6
Insertion loss		
RC 5-40MHz	dB	4
TV 47-862MHz	dB	4.5
SAT 950-1750MHz	dB	5
SAT 1750-2150MHz	dB	5.5
SAT 2150-2400MHz	dB	7
Tap loss		
RC 5-40MHz	dB	16
TV 47-862MHz	dB	16
SAT 950-1750MHz	dB	16
SAT 1750-2150MHz	dB	16
SAT 2150-2400MHz	dB	16
Outputs Isolation		
RC 5-40MHz	dB	25
TV 47-862MHz	dB	25
SAT 950-1750MHz	dB	24
SAT 1750-2150MHz	dB	22
SAT 2150-2400MHz	dB	21

Specifications		
Tap loss	dB	16
Dimensions and packaging		
Pieces		1
EAN code		8016978095018
Packaging dimensions	mm	125 x 65 x 30
Product dimensions	mm	126 x 64 x 27
Packaging weight	Kg	0.146