


## TAPS620

### Taps and splitters

6-output "top-down" horizontal tap with 20dB attenuation and F connector for TV and Satellite band (5-2400MHz).



### Technical Chars

- The elegant and compact design allows installation in any junction box.
- The **die-cast zinc** products in this series ensure high performance, with very low insertion losses even at SAT frequencies and high isolation between outputs.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the through output and input.**

| TAPS620           |    |        |
|-------------------|----|--------|
| Code              |    | 287320 |
| Taps              |    | 6      |
| Insertion loss    |    |        |
| RC 5-40MHz        | dB | 2.5    |
| TV 47-862MHz      | dB | 2.5    |
| SAT 950-1750MHz   | dB | 3      |
| SAT 1750-2150MHz  | dB | 4.5    |
| SAT 2150-2400MHz  | dB | 5.5    |
| Tap loss          |    |        |
| RC 5-40MHz        | dB | 20     |
| TV 47-862MHz      | dB | 20     |
| SAT 950-1750MHz   | dB | 20     |
| SAT 1750-2150MHz  | dB | 20     |
| SAT 2150-2400MHz  | dB | 20     |
| Outputs Isolation |    |        |
| RC 5-40MHz        | dB | 24     |
| TV 47-862MHz      | dB | 24     |
| SAT 950-1750MHz   | dB | 24     |
| SAT 1750-2150MHz  | dB | 22     |
| SAT 2150-2400MHz  | dB | 21     |

| Specifications           |    |               |
|--------------------------|----|---------------|
| Tap loss                 | dB | 20            |
| Dimensions and packaging |    |               |
| Pieces                   |    | 1             |
| EAN code                 |    | 8016978095025 |
| Packaging dimensions     | mm | 126 x 64 x 27 |
| Product dimensions       | mm | 126 x 64 x 27 |
| Packaging weight         | Kg | 0.146         |