

TAPS816

Taps and splitters





Technical Chars

- The elegant and compact design allows installation in any junction box.
- The **die-cast zinc** products in this series ensure high performance, with very low insertion losses even at SAT frequencies and high isolation between outputs.
- Prepared for earth connection and wall mounting.
- DC is allowed to pass between the through output and input.

| TA DO01 6 | | |
|-------------------|----|--------|
| TAPS816 | | |
| Code | | 287321 |
| Taps | | 8 |
| Insertion loss | | |
| RC 5-40MHz | dB | 4.5 |
| TV 47-862MHz | dB | 5 |
| SAT 950-1750MHz | dB | 5.5 |
| SAT 1750-2150MHz | dB | 5.5 |
| SAT 2150-2400MHz | dB | 7 |
| Tap loss | | |
| RC 5-40MHz | dB | 16 |
| TV 47-862MHz | dB | 16 |
| SAT 950-1750MHz | dB | 16 |
| SAT 1750-2150MHz | dB | 16 |
| SAT 2150-2400MHz | dB | 16 |
| Outputs Isolation | | |
| RC 5-40MHz | dB | 23 |
| TV 47-862MHz | dB | 23 |
| SAT 950-1750MHz | dB | 22 |
| SAT 1750-2150MHz | dB | 21 |
| SAT 2150-2400MHz | dB | 20 |



| Specifications | | |
|--------------------------|----|---------------|
| Tap loss | dB | 16 |
| Dimensions and packaging | | |
| Pieces | | 1 |
| EAN code | | 8016978095032 |
| Packaging dimensions | mm | 126 x 64 x 27 |
| Product dimensions | mm | 126 x 64 x 27 |
| Packaging weight | Kg | 0.15 |