

## **TAPS820**

Taps and splitters





## **Technical Chars**

- The elegant and compact design allows installation in any junction box.
- The **die-cast zinc** products in this series ensure high performance, with very low insertion losses even at SAT frequencies and high isolation between outputs.
- Prepared for earth connection and wall mounting.
- DC is allowed to pass between the through output and input.

TAPS820		
Code		287322
Taps		8
Insertion loss		
RC 5-40MHz	dB	2.5
TV 47-862MHz	dB	3
SAT 950-1750MHz	dB	3
SAT 1750-2150MHz	dB	4.5
SAT 2150-2400MHz	dB	5.5
Tap loss		
RC 5-40MHz	dB	20
TV 47-862MHz	dB	20
SAT 950-1750MHz	dB	20
SAT 1750-2150MHz	dB	20
SAT 2150-2400MHz	dB	20
Outputs Isolation		
RC 5-40MHz	dB	24
TV 47-862MHz	dB	23
SAT 950-1750MHz	dB	23
SAT 1750-2150MHz	dB	22
SAT 2150-2400MHz	dB	21



Specifications			
Tap loss	dB	20	
Dimensions and packaging			
Pieces		1	
EAN code		8016978095049	
Packaging dimensions	mm	126 x 64 x 27	
Product dimensions	mm	126 x 64 x 27	
Packaging weight	Kg	0.15	