

## SWP932TS

## **Compact**



**9-input compact** multiswitch with **32 output taps**; DIP switch to select **active and passive TV gain**.

## **Technical Chars**

- Satellite band up to 2300MHz.
- High output level to cover long cable distances (60m with 6.7mm cable).
- Each port has an LED to show correct reception of DiSEqC commands.
- Return channel included when TV gain is passive (5-65MHz).
- When TV gain is passive, the product is fully powered by the receivers, the power supply only serves to power the active TV gain, other amplifiers and LNBs.
- External PSU1215TS power supply (12V, 1.5A) included in the package with Male Jack connector (2.1x5.5x12; inside positive, outside negative) to optimise installation space and reduce maintenance time.
- Small size due to matrix switching system with connectors on both sides.
- · Easy to install thanks to standard input colouring.

SWP932TS		
Code		287354
Inputs		8 SAT, 1 TV
Taps		32
SAT		
Bandwidth	MHz	950-2300
Gain	dB	-7/-2
Max Output level	dΒμV	100
TV		
TV bandwidth	MHz	Active TV: 47-862; Passive TV: 5-862
Gain (Active)	dB	-4
Gain (Passive)	dB	-24
Max Output level	dΒμV	Active TV gain: 95
Return channel		
Bandwidth	MHz	Passive TV: 5-65