

SWA1730TS

Line amplifiers



Head or line amplifier with 17 inputs (16 Satellite and 1 TV) and gain adjustment.

Technical Chars

- High Satellite amplification.
- **Gain** adjustment for TV input.
- Dip switch to select **active or passive TV** gain.
- Gain adjustment for each Satellite input.
- Satellite bandwidth up to 2300MHz.
- High Satellite output level.
- **Power supply from feed-through lines** (independently on each port) or from side female **Jack connector**, each port has an LED to show its correct power supply.
- Ideal for small and medium sized installations.
- Compact size.
- Easy to install due to standard input colouring.

SWA1730TS		
Code		287374
Inputs		16 SAT, 1 TV
Outputs		16 SAT, 1 TV
SAT		
Bandwidth	MHz	950-2300
Gain	dB	30
Gain adjustment	dB	20
Max Output level	dB μ V	112
TV		
TV bandwidth	MHz	Active TV: 47-862; Passive TV: 5-862
Gain (Active)	dB	18
Gain adjustment	dB	20
Gain (Passive)	dB	-2
Max Output level	dB μ V	Active TV: 110

Consumption		
Power supply voltage	V	12-14
Absorption	mA	Active TV: 2150 @13V; Passive TV: 2000 @13V
Specifications		
Operating temperature	°C	-10 to +55
Dimensions and packaging		
Pieces		1
EAN code		8016978097227
Packaging dimensions	mm	156 x 260 x 45
Product dimensions	mm	290 x 120 x 40
Packaging weight	Kg	0.6