

FR 4EASY

Measurement tools



Combined Satellite DVB-S/S2 TV DVB-T/T2 and CATV DVB-C **Field Meters** with 4".

Complete with DiSEqC, with SCR and DCSS protocols (SCD2) and wideband (optional) . MPEG 2 video compression with Full HD or SD picture quality. The metal body gives the meter a robustness suitable for installation use.

Technical Chars

- Accurate and easy to use
- DVB-S/S2, DVB-T, DVB-C
- All digital measurements
- DiSEqC , SCR and dCSS
- MPEG 2-4 SD and FULL HD images
- Analog TV measurements
- Automemory and autoquality
- Spectrum with memory peak
- Rugged metal body
- water-proof bag
- Long life LI-PO batteries
- NOTE: Check for APP supplied and optional

FR 4EASY		
Code		287431
Display		4.3"
Battery	V/Ah	2000mAh
Power supply voltage	Vdc/A	220-240 / 50-60 Alimentatore in dotazione
uscita/e - lcn		USB Type B
Frequency	MHz	44-880, 950-2610
TV Input power	dBμV	10 - 100
SAT input power	dBμV	28 - 92
Optical input		No
Digital image		MPEG 2 and 4 SD and HD with Service list, LCN and video Bit Rate
Digital measurement		Digital signal power
Standard DVB		DVB-S/S2, DVB-T, DVB-C
Analog video		Measure Only
MER	dB	Channel MER
Constellation		Only Sat
Memory		2000 Storage Transponders (SAT) World TV Channels
Settable memory		Programmable from PC or instrument
Data logger		Yes
Remote feeding	mA	5-12-18-24 DiSEqC, SCR, dCSS (SCD2)
Specifications		
Power supply voltage	Vdc/A	220-240 / 50-60 Alimentatore in dotazione
Dimensions and packaging		
Pieces		1
EAN code		8016978100309
Product dimensions	mm	113 x 185 x 144
Weight	kg	1