

PA2M

Taps and splitters

2-output clamp splitter of the PAM series in the TV and Satellite band (5-2400MHz).



Technical Chars

- Thanks to the **unique retaining clip**, the central connector remains integral with the rest of the mechanics, facilitating cable attachment.
- The **very small dimensions** and the clamp solution, without an F connector, considerably reduce the installation footprint.
- The **excellent shielding** guarantees the protection of the signal from **5G and 4G LTE** disturbances in the air.
- The **new mechanics with protective fins (Rev. 1)** prevent the spring of the central connector from being accidentally pressed while closing the junction boxes.
- **DC pass** from output to input ports on all the products.

PA2M		
Code		287456
Outputs		2
Insertion loss		
RC 5-40MHz	dB	4
TV 47-862MHz	dB	4.3
SAT 950-1750MHz	dB	5.1
SAT 1750-2150MHz	dB	5.8
SAT 2150-2400MHz	dB	6.8
Outputs Isolation		
RC 5-40MHz	dB	21
TV 47-862MHz	dB	21
SAT 950-1750MHz	dB	21
SAT 1750-2150MHz	dB	21
SAT 2150-2400MHz	dB	20

Dimensions and packaging		
Pieces		10
EAN code		8016978101184
Multiple EAN		8016978101504
Packaging dimensions	mm	130 x 75 x 90
Product dimensions	mm	62 x 33 x 23
Packaging weight	Kg	0.66