


## PA4M

Taps and splitters





## **Technical Chars**

- Thanks to the **unique retaining clip**, the central connector remains integral with the rest of the mechanics, facilitating cable attachment.
- The **very small dimensions** and the clamp solution, without an F connector, considerably reduce the installation footprint.
- The excellent shielding guarantees the protection of the signal from 5G and 4G LTE disturbances in the air.
- The **new mechanics with protective fins (Rev. 1)** prevent the spring of the central connector from being accidentally pressed while closing the junction boxes.
- DC pass from output to input ports on all the products.

PA4M			
Code		287458	
Outputs		4	
Insertion loss			
RC 5-40MHz	dB	8.1	
TV 47-862MHz	dB	8.7	
SAT 950-1750MHz	dB	9.6	
SAT 1750-2150MHz	dB	10.5	
SAT 2150-2400MHz	dB	11.5	
Outputs Isolation			
RC 5-40MHz	dB	21	
TV 47-862MHz	dB	21	
SAT 950-1750MHz	dB	21	
SAT 1750-2150MHz	dB	21	
SAT 2150-2400MHz	dB	20	

## **Data sheet**



Dimensions and packaging		
Pieces		10
EAN code		8016978101207
Multiple EAN		8016978101481
Packaging dimensions	mm	130 x 75 x 90
Product dimensions	mm	82 x 33 x 23
Packaging weight	Kg	0.96