


## PA<sub>5</sub>M

Taps and splitters





## **Technical Chars**

- Thanks to the **unique retaining clip**, the central connector remains integral with the rest of the mechanics, facilitating cable attachment.
- The **very small dimensions** and the clamp solution, without an F connector, considerably reduce the installation footprint.
- The excellent shielding guarantees the protection of the signal from 5G and 4G LTE disturbances in the air.
- The **new mechanics with protective fins (Rev. 1)** prevent the spring of the central connector from being accidentally pressed while closing the junction boxes.
- DC pass from output to input ports on all the products.

PA5M		
Code		287459
Outputs		5
Insertion loss		
RC 5-40MHz	dB	10.6
TV 47-862MHz	dB	11.2
SAT 950-1750MHz	dB	12.7
SAT 1750-2150MHz	dB	13.5
SAT 2150-2400MHz	dB	16.5
Outputs Isolation		
RC 5-40MHz	dB	21
TV 47-862MHz	dB	21
SAT 950-1750MHz	dB	21
SAT 1750-2150MHz	dB	21
SAT 2150-2400MHz	dB	20

## **Data sheet**



Dimensions and packaging		
Pieces		10
EAN code		8016978101214
Multiple EAN		8016978101474
Packaging dimensions	mm	130 x 75 x 90
Product dimensions	mm	82 x 33 x 23
Packaging weight	Kg	0.96