

DE110M

Taps and splitters

1-output clamp tap with 10dB attenuation of the DEM Series in the TV and Satellite band (5-2400MHz).



Technical Chars

- Thanks to the **unique retaining clip**, the center connector remains integral with the rest of the mechanics, facilitating cable attachment.
- The **very small size** and clamp solution, without an F connector, greatly reduce the installation footprint.
- **Excellent shielding** ensures signal protection from **5G and 4G LTE** disturbances in the air.
- **New mechanics with protective fins (Rev. 1)** prevent the center connector clip from being accidentally pressed while closing the junction boxes.
- **Separate input and output ports** so that different diameter cables can be used between the down conductor and the branch outlets.
- **DC pass-through** from the outputs to the input throughout the series; DC blocking in the branch outputs of DE models.

DE110M		
Code		287460
Taps		1
Insertion loss		
RC 5-40MHz	dB	1.6
TV 47-862MHz	dB	1.7
SAT 950-1750MHz	dB	2
SAT 1750-2150MHz	dB	2.5
SAT 2150-2400MHz	dB	3
Tap loss		
RC 5-40MHz	dB	10
TV 47-862MHz	dB	10
SAT 950-1750MHz	dB	10.5
SAT 1750-2150MHz	dB	11
SAT 2150-2400MHz	dB	11.5

Outputs Isolation		
RC 5-40MHz	dB	20
TV 47-862MHz	dB	20
SAT 950-1750MHz	dB	20
SAT 1750-2150MHz	dB	20
SAT 2150-2400MHz	dB	20
Specifications		
Tap loss	dB	10
Dimensions and packaging		
Pieces		10
EAN code		8016978101221
Multiple EAN		8016978101467
Packaging dimensions	mm	130 x 75 x 90
Product dimensions	mm	62 x 33 x 23
Packaging weight	Kg	0.66