

DE210M

Taps and splitters

2-output clamp tap with 10dB attenuation of the DEM series in the TV and Satellite band (5-2400MHz).



Technical Chars

- Thanks to the **unique retaining clip**, the center connector remains integral with the rest of the mechanics, facilitating cable attachment.
- The **very small size** and clamp solution, without an F connector, greatly reduce the installation footprint.
- **Excellent shielding** ensures signal protection from **5G and 4G LTE** disturbances in the air.
- **New mechanics with protective fins (Rev. 1)** prevent the center connector clip from being accidentally pressed while closing the junction boxes.
- **Separate input and output ports** so that different diameter cables can be used between the down conductor and the branch outlets.
- **DC pass-through** from the outputs to the input throughout the series; DC blocking in the branch outputs of DE models.

| DE210M | | |
|------------------|----|--------|
| Code | | 287464 |
| Taps | | 2 |
| Insertion loss | | |
| RC 5-40MHz | dB | 3.5 |
| TV 47-862MHz | dB | 3.5 |
| SAT 950-1750MHz | dB | 4.5 |
| SAT 1750-2150MHz | dB | 5 |
| SAT 2150-2400MHz | dB | 5.5 |
| Tap loss | | |
| RC 5-40MHz | dB | 10 |
| TV 47-862MHz | dB | 10 |
| SAT 950-1750MHz | dB | 10.5 |
| SAT 1750-2150MHz | dB | 11 |
| SAT 2150-2400MHz | dB | 11.5 |

| Outputs Isolation | | |
|--------------------------|----|---------------|
| RC 5-40MHz | dB | 20 |
| TV 47-862MHz | dB | 20 |
| SAT 950-1750MHz | dB | 20 |
| SAT 1750-2150MHz | dB | 20 |
| SAT 2150-2400MHz | dB | 20 |
| Specifications | | |
| Tap loss | dB | 10 |
| Dimensions and packaging | | |
| Pieces | | 10 |
| EAN code | | 8016978101269 |
| Multiple EAN | | 8016978101429 |
| Packaging dimensions | mm | 130 x 75 x 90 |
| Product dimensions | mm | 62 x 33 x 23 |
| Packaging weight | Kg | 0.66 |