

PA2ME

Taps and splitters



PAM series 2-way pole-mounted terminal partition in TV and Satellite band (5-2400MHz) on outdoor BOM enclosure, with pole clamp included.

Technical Chars

- Thanks to the **unique retaining clip**, the center connector remains integral with the rest of the mechanics, facilitating cable attachment.
- The **very small size** and clamp solution, without an F connector, greatly reduce the installation footprint.
- **Excellent shielding** ensures signal protection from **5G and 4G LTE** disturbances in the air.
- **New mechanics with protective fins (Rev. 1)** prevent the center connector clip from being accidentally pressed while closing the junction boxes.
- **DC pass-through** from the outputs to the input throughout the series.

PA2ME		
Code		287619
Outputs		2
Insertion loss		
RC 5-40MHz	dB	4
TV 47-862MHz	dB	4.3
SAT 950-1750MHz	dB	5.1
SAT 1750-2150MHz	dB	5.8
SAT 2150-2400MHz	dB	6.8
Outputs Isolation		
RC 5-40MHz	dB	21
TV 47-862MHz	dB	21
SAT 950-1750MHz	dB	21
SAT 1750-2150MHz	dB	21
SAT 2150-2400MHz	dB	20

Dimensions and packaging		
Pieces		1
EAN code		8016978106165
Packaging dimensions	mm	125 x 108 x 40
Product dimensions	mm	115 x 90 x 35
Packaging weight	Kg	0.19