

FSW-24GE4SFPPOE

Switch/router



Switch Layer 2+ in grado di fornire flessibilità, prestazioni e scalabilità.

Le 24 porte GE PoE consentono di alimentare dispositivi in campo come telecamere di videosorveglianza IP e access point.

Le 4 porte SFP+ a 10GE permettono il collegamento stack o uplink con altri switch della stessa serie.

Caratteristiche tecniche

- Layer 2+
- 24 porte 10/100/1000 GE POE
- 4 porte di uplink SFP+ 10GE
- Backplane 128Gbps
- Forwarding rate 96Mpps
- QoS & QinQ
- Fino a 4096 VLAN
- Multicast

FSW-24GE4SFPPOE		
Codice		287626
Ingresso LAN	24x 10/100/1000M auto-negoziabile POE, 4x SFP+	
Console RJ45	RJ45	1
Backplane	Gbps	128
Forwarding rate	Mpps/64bytes	96
Ventole	2	
Noise@25°C	dBa	37.5
Forwarding mode	Store-forward	
Memoria flash	MB	32
Memoria DRAM	MB	256
MAC		16k
Buffer size	MB	1.5
Interfacce VLAN		64
Routing table	RIB	2040
MTBF	h	>50000

Funzioni		
Management		Console, Telnet, SSH v1/v2, HTTP, HTTPS, SNMP v1/v2/v3, RMON
Applicazioni		<ul style="list-style-type: none"> Spanning Tree: 802.1D (STP), 802.1W (RSTP) and 802.1S (MSTP), BPDU guard, root guard and loopback guard IP. Static route, RIP, OSPF, IPv4/IPv6 dual stack IPv6: ICMPv6, DHCPv6, ACLv6 and IPv6 Telnet, IPv6 neighbor discovery, Path MTU, Discovery, MLD V1, MLD snooping, IPv6 Static Routing, RIPng, OSPFv3, Manual tunnel, ISATAP tunnel, 6 to 4 tunnel Reliability: Static/LACP link aggregation, Interfaccia di backup, EAPS and ERPS, ISSU uninterrupted system upgrade, BVSS, up to 16-units per stack, VRRP, UDLD
VLAN		4096 Active VLAN, QinQ & Selective QinQ, GVRP, Private VLAN & Voice-VLAN
MULTICAST		Support IGMP v1/v2/v3, IGMP Snooping, IGMP Fast Leave, MVR, IGMP filter
QoS		CAR, HQoS, MAC/IP/TCP/UDP/ VLAN/ COS/ DSCP/ TOS based QoS, 802.1P/DSCP priority re-labeling, SP, WRR and "SP+WRR", Tail-Drop, WRED, flow monitoring and traffic shaping
DHCP		<ul style="list-style-type: none"> DHCP server/relay/client DHCP snooping/option82
Security		<ul style="list-style-type: none"> Port isolation, Port security, and "IP+MAC+port" binding, MAC sticky DAI & IP source guard PPPoE+ IEEE 802.1x, AAA, Radius and BDTacacs+ L2/L3/L4 ACL flow identification and filtration Anti-attack from DDoS, TCP's SYN, Flood, UDP Flood Broadcast/multicast/unknown unicast stormcontrol - MD5, SHA-256, RSA-1024, AES256
Caratteristiche principali		
Tensione alimentazione	Vdc/A	100-240 / 50-60
Consumo	W	<408
Temperatura lavoro	°C	Da 0 a +50
Umidità relativa	%	da 10 a 90 (senza condensa)
Dimensioni e imballo		
codice EAN		8016978106561
Dimensioni imballo	mm	555 x 295 x 88
Dimensioni prodotto	mm	440 x 210 x 44
Peso lordo	Kg	4.1
Peso	Kg	3