

FSW-24GE4SFP

Switches/routers



Layer 2+ switches capable of providing flexibility, performance and scalability.

The 24 GE ports enable distributed network points to be connected in common areas, offices, etc.

The 4 SFP+ ports at 10GE allow stack or uplink with other switches in the same series.

Technical Chars

- Layer 2+
- 24 10/100/1000 GE ports
- 4 SFP+ 10GE uplink ports
- 128Gbps backplane
- Forwarding rate 96Mpps
- QoS & QinQ
- Up to 4096 VLANs
- Multicast

FSW-24GE4SFP		
Code		287627
LAN input		24 x 10/100/1000M auto-negotiation, 4 x SFP+
RJ45 console	RJ45	1
Backplane	Gbps	128
Forwarding rate	Mpps/64bytes	96
Fans		0
Noise@25°C	dBA	0
Forwarding mode		Store-forward
Flash memory	MB	32
DRAM memory	MB	256
MAC		16k
Buffer size	MB	1.5
VLAN Interface		64
Routing table	RIB	2040
MTBF	h	>50000

Functions		
Management		Console, Telnet, SSH v1/v2, HTTP, HTTPS, SNMP v1/v2/v3, RMOM
Applications		<ul style="list-style-type: none"> Spanning Tree: 802.1D (STP), 802.1W (RSTP) and 802.1S (MSTP), BPDU guard, root guard and loopback guard IP. Static route, RIP, OSPF, IPv4/IPv6 dual stack IPv6: ICMPv6, DHCPv6, ACLv6 and IPv6 Telnet, IPv6 neighbour discovery, Path MTU, Discovery, MLD V1, MLD snooping, IPv6 Static Routing, RIPng, OSPFv3, manual tunnel, ISATAP tunnel, 6 to 4 tunnel Reliability: Static/LACP link aggregation, backup interface, EAPS and ERPS, ISSU uninterrupted system upgrade, BVSS, up to 16 units per stack, VRRP, UDLD
VLAN		4096 active VLAN, QinQ & selective QinQ, GVRP, private VLAN & Voice-VLAN
MULTICAST		Support IGMP v1/v2/v3, IGMP Snooping, IGMP Fast Leave, MVR, IGMP filter
QoS		CAR, HQoS, MAC/IP/TCP/UDP/ VLAN/ COS/ DSCP/ TOS based QoS, 802.1P/DSCP priority re-labeling, SP, WRR and "SP+WRR", Tail-Drop, WRED, flow monitoring and traffic shaping
DHCP		<ul style="list-style-type: none"> DHCP server/relay/client DHCP snooping/option82
Security		<ul style="list-style-type: none"> Port isolation, Port security, and "IP+MAC+port" binding, MAC sticky DAI & IP source guard PPPoE+ IEEE 802.1x, AAA, Radius and BDTacacs+ L2/L3/L4 ACL flow identification and filtration Anti-attack from DDoS, TCP's SYN, Flood, UDP Flood Broadcast/multicast/unknown unicast stormcontrol - MD5, SHA-256, RSA-1024, AES256
Specifications		
Power supply voltage	Vdc/A	100-240 / 50-60
Current consumption	W	35
Operating temperature	°C	0 to +50
Relative humidity	%	from 10 to 90 (without condensation)
Dimensions and packaging		
EAN code		8016978106578
Packaging dimensions	mm	500 x 320 x 80
Product dimensions	mm	440 x 180 x 44
Packaging weight	Kg	3.9
Weight	Kg	2.6