

GX-4S2FTA-BP-01

Galaxia headend



GX-4S2FTA-BP-01 module is the multi-inputs FTA Satellite receiver able to tune up to **four independent DVB-S/S2/S2X Free-To-Air satellite transponders** and share and pool the contents to the GALAXIA main chassis.

Technical Chars

- 4 independent SAT inputs(DVB-S/S2/S2X FTA)
- **Independent LNB remote feed** for each RF input
- **"Hot-swappable"** module
- **On-board WEB interface:** programming of all parameters is easily done via HTML web interface

GX-4S2FTA-BP-01		
Code		287636
Inputs		
Input no.		4
Front-end		
Input no.		4 independent SAT inputs
Input band	MHz	950-2150
Input level	dB μ V	38-88
LNB controls		DiSEqC 1.0
Remote feeding	mA	400 max
Demodulators		<ul style="list-style-type: none"> • DVB-S: QPSK, 8PSK • DVB-S2: QPSK, 8PSK, 16APSK, 32APSK • DVB-S2X: QPSK, 8PSK, 16APSK, 32APSK, 64APSK
FEC		<ul style="list-style-type: none"> • DVB-S: 1/2, 2/3, 3/4, 5/6, 7/8 • DVB-S2: 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 • DVB-S2X: 11/15, 7/9, 4/5, 5/6 (Normal FECFRAME)
Symbol rate	MS/s	DVB-S: from 1 to 45 DVB-S2: from 1 to 45 DVB-S2X: from 1 to 34
Specifications		
Connectors		4x F-female (RF)
Current consumption	W	30
Common interface		Not available
Operating temperature	$^{\circ}$ C	-5 to +50

