

RK36U 68P

Rack



The Rack 19" 600x800 36U PRO cabinet, due to its stability and load capacity, is designed for the set-up of technical areas in small spaces and the installation of telecommunications, IT and audio/video equipment. Its depth allows for both front and rear working of the cabinet in order to maximise its capacity. Its fully dismountable structure and easy re-assembly make it ideal in the presence of architectural barriers. The cabinet is supplied assembled.

Technical Chars

- Steel frame
- 2 adjustable uprights supplied and 2 optional
- Tempered glass front door
- Removable side and rear panels
- Pre-arrangement on roof for installation of ventilation system
- Provision for cable access from below and above
- Adjustable feet

initial_fields		
Code		287678
Specifications		
Unit		36U
Net Weight	Kg	81
Load capacity	kg	600
Base and roof structure		
Material		Sheet steel
Thickness	mm	15/10
Predisposition		Pre-cut base for cable entry and roof for cooling fan installation.
External uprights		
Material		Sheet steel
Quantity		4
Thickness	mm	20/10
Side panels		
Typology		Removable with quick release 1/4 turn key
Quantity		2
Thickness	mm	12/10

Rear panel		
Typology		Removable with quick release 1/4 turn key
Thickness	mm	12/10
Front door		
Typology		Tempered glass
Handle		Ergonomic retractable with key
Opening angle	°	130
Internal uprights		
Typology		Depth adjustable
Quantity		4
Material		Galvanised steel
Thickness	mm	20/10
Floor supports		
Typology		Adjustable feet
Quantity		4
Varnishing- rack		
Typology		Epoxy-polyester
RAL		9005
Colour		Black
Packaging		
Pieces		1
EAN code		8016978107162
Packaging dimensions	mm	700 x 900 x 1885

Rack cabinet details

- A. Roof rack cabinet
- B. Galvanised internal upright
- C. Side panel closing detail
- D. Removable side panel
- E. Front door opening



A.



B.



C.



D.



E.