

RK36U 66P

Rack



The Rack 19" 600x800 36U PRO cabinet, due to its stability and load capacity, is designed for the set-up of technical areas in small spaces and the installation of telecommunications, IT and audio/video equipment. The fully demountable and easy to re-assemble structure makes it ideal in the presence of architectural barriers. The cabinet is supplied assembled.

Technical Chars

- Steel frame
- 2 adjustable uprights supplied and 2 optional
- Tempered glass front door
- Removable side and rear panels
- Pre-arrangement on roof for installation of ventilation system
- Provision for cable access from below and above
- Adjustable feet

RK36U 66P			
Code		287679	
Specifications			
Unit		36U	
Product dimensions	mm	600 x 600 x 1735	
Net Weight	kg	71	
Load capacity	kg	400	
Base and roof structure			
Material		Sheet steel	
Thickness	mm	15/10	
Predisposition		Pre-cut base for cable entry and roof for cooling fan installation.	
External uprights			
Material		Sheet steel	
Quantity		4	
Thickness	mm	20/10	
Side panels			
Typology		Removable with quick release 1/4 turn key	
Quantity		2	
Thickness	mm	12/10	



Rear panel			
Typology		Removable with quick release 1/4 turn key	
Thickness	mm	12/10	
Front door			
Typology		Tempered glass	
Handle		Ergonomic retractable with key	
Opening angle	۰	130	
Internal uprights			
Typology		Depth adjustable	
Quantity		2	
Material		Galvanised steel	
Thickness	mm	20/10	
Floor supports			
Typology		Adjustable feet	
Quantity		4	
Varnishing- rack			
Typology		Epoxy-polyester	
RAL		9005	
Colour		Black	
Packaging			
Pieces		1	
EAN code		8016978107179	
Packaging dimensions	mm	700 x 700 x 1885	

Rack cabinet details

- A. Roof rack cabinet
- B. Galvanised internal upright
- C. Side panel closing detail
- D. Removable side panel
- E. Front door opening



