

## RK42U 68S

### Rack



The Rack 19" 600x800 42U PRO cabinet, due to its stability and load capacity, is designed for the set-up of technical areas in small spaces and the installation of telecommunications, IT and audio/video equipment. Its depth allows for both front and rear working of the cabinet in order to maximise its capacity. Its fully dismountable structure and easy re-assembly make it ideal in the presence of architectural barriers. The cabinet is supplied assembled.

### Technical Chars

- Steel frame
- 4 adjustable uprights
- Tempered glass front door
- Removable side and rear panels
- Pre-arrangement on roof for installation of ventilation system
- Provision for cable access from below and above
- Adjustable feet

RK42U 68S		
Code		287683
Specifications		
Unit		42U
Product dimensions	mm	600 x 800 x 2000
Net Weight	kg	92
Load capacity	kg	600
Base and roof structure		
Material		Sheet steel
Thickness	mm	15/10
Predisposition		Pre-cut base for cable entry and roof for cooling fan installation.
External uprights		
Material		Sheet steel
Quantity		4
Thickness	mm	20/10
Side panels		
Typology		Removable with quick release 1/4 turn key
Quantity		2
Thickness	mm	12/10

<b>Rear panel</b>		
Typology		Removable with quick release 1/4 turn key
Thickness	mm	12/10
<b>Front door</b>		
Typology		Tempered glass
Handle		Ergonomic retractable with key
Opening angle	°	130
<b>Internal uprights</b>		
Typology		Depth adjustable
Quantity		4
Material		Galvanised steel
Thickness	mm	20/10
<b>Floor supports</b>		
Typology		Adjustable feet
Quantity		4
<b>Varnishing- rack</b>		
Typology		Epoxy-polyester
RAL		9005
Colour		Black
<b>Packaging</b>		
Pieces		1
EAN code		8016978107216
Packaging dimensions	mm	700 x 900 x 2150

## Rack cabinet details

- A. Roof rack cabinet
- B. Galvanised internal upright
- C. Side panel closing detail
- D. Removable side panel
- E. Front door opening



A.



B.



C.



D.



E.